




Features & Benefits

- Ultra-flexible with stranded inner conductor
- Available in ruggedized armor
- Multi-layer protection, robust for test use
- Very good phase stability over flexure $< \pm 5^\circ$ to 26.5GHz

Cable Construction



No.	Construction	Size (mm)	Materials
1	Center Conductor	1.02	Stranded silver plated copper
2	Dielectric	3.03	LD PTFE wrapping
3	Outer Conductor	3.22	Silver plated copper strip wrapping
4	Interlayer	3.47	PTFE
5	Outer Shield	4.05	Silver plated copper wire braiding
6	Jacket	5.20	PUR or FEP



Electrical

Frequency	DC-26.5 GHz
Impedance	50 Ω
Velocity of Propagation	76%
Shielding Effectiveness	>90 dB
Withstanding Voltage	2000 V
*Mechanical Phase Stability	$< \pm 4^\circ @ 18\text{GHz}$, $< \pm 5^\circ @ 26.5\text{GHz}$
Amplitude Stability vs Shaking	$< \pm 0.1\text{dB}$
* Wrapped 360° around a 52mm radius mandrel.	

Mechanical & Environmental

Min. Bending Radius Static	18mm
Min. Bending Radius Repeated	50mm
Weight	55g/m
Operation Temp(PUR Jacket)	-50 ~ 85 °C
Operation Temp(FEP Jacket)	-50 ~ 150 °C

Attenuation(Typical@25°C&VSWR=1.0) & Power(VSWR=1.0; 40°C; Sea level)

Frequency MHz	300	1000	2000	4000	6000	8000	10000	12000	14000	16000	18000	26500
dB/100 Meter	20.4	38.5	55.9	82.0	103.2	121.9	139.0	154.9	169.9	184.2	198.0	252.1
Avg.Power kW	0.830	0.441	0.304	0.207	0.164	0.139	0.122	0.110	0.100	0.092	0.086	0.067
Attenuation at any frequency = $[1.136600 \times \text{SQRT}(\text{FMHz})] + [0.002530 \times \text{FMHz}]$												